

Technical Data Sheet: IB Clad Metal Scupper

Product Description: IB Clad Metal Scuppers are custom fabricated out of a 24 ga. Galvanized/ bonded 25 mil. IB Single Ply membrane metal to your exact specification needs and have a factory welded, non-reinforced IB Single-Ply Flashing Target that allows for easy application over the newly installed IB roof system. IB Clad Metal Scuppers design incorporates a large metal tab flange that can be fastened through to a suitable substrate using an approved fastener.

Advantages:

- Custom factory fabricated flashing eliminates the errors of a field fabricated drain
- Easily attachable to the substrate
- Simple and easy to install from rooftop

Installation Instructions: Position drain through opening and install two approved fasteners per flange (4 per drain) to the substrate. Clean off any residue, dirt or other contaminates from the bottom of the IB Clad Metal Scupper and the roof surfaces and hot air weld the perimeter target. Seal outer drain body (minimum of 1") to the exterior wall and install conductor head and downspout.

Packaging: Individually or 25 per box.

Available Colors: Available in all IB membrane and DeckShield colors.



Technical Data Sheet: IB Drain Liner

Product Description: IB Drain Liners are 2" and 3" factory fabricated round straight tube body's with a reinforced IB Single-Ply Flashing Target that allows for easy application over the newly installed IB roof system using either with a galvanized sheet metal drain body or without. IB Drain Liners are ideal for use at ponding conditions at over-hangs that will allow for the installation of a conductor head and down spout/ drain line.

Advantages:

- Factory fabricated flashing eliminates the errors of a field fabricated drain
- Easily attachable to the substrate
- Simple and easy to install from rooftop

Installation Instructions: Install the new IB roof system (field and base flashing membranes. Position drain through the opening. Clean off any residue (dirt or other contaminates from the bottom of the IB Drain Liner and the IB roof surfaces) and hot air weld the perimeter target. Seal outer drain body (length determined by the designer of record, typical minimum of 1") to the exterior wall and install conductor head and downspout.

Packaging: Individually or 25 per box.

Available Colors: Available in all IB membrane and DeckShield colors.



Drain Liner Specifications			
Type of Drain Liner	Base Target	Diameter	Tube Length
2" Drain Liner	12" x 12"	2"	12"
3" Drain Liner	12" x 12"	3"	12"